

The logo for CRAIG features the word "CRAIG" in a bold, blue, sans-serif font. A blue curved line arches over the letters from the top left to the top right.

Adhesives and Coatings

ISO 9001-2000 Certified
The Chemistry of Customer Attention

80 Wheeler Point Rd.
Newark NJ, 07105

Phone: (973) 344-1483
Fax: (973) 344-4767
www.craigadhesives.com

CRAIGBOND 3719A

Application

Spine, pocket, collating and general purpose water based adhesive.

Provides excellent bonds on difficult-to-bond substrates. Yields superior mileage, tack range, non-warping, non-skinning for excellent machining and clean up.

Used on extrusion for backbone, pattern print for pocket.

Excellent on uncoated stock providing less curl. Super balance of tack, speed and machining for even the newest, fastest production lines.

Excellent pan stability with very little foaming and clean up required. General purpose adhesive for coated, high bulk and offset.

Physical Properties

APPEARANCE: White liquid, dries clear

VISCOSITY: 1000-1200CPS (Brookfield, 20 rpm, #4 spindle, 77°F)

WEIGHT /GALLON(LBS): 9.1

SOLIDS: 65+/- 3%

pH: 4.5-6.0

REPULPABLE: Yes

Calculated VOC: 3.42%

CLEAN UP: Warm, soapy water while still wet

STORAGE CONDITIONS: Store below 90°F. Keep from freezing and excessive heat and cold. If very cold, product should be warmed slowly. Low temperatures will thicken product; high temperatures will thin product. If frozen, product is unusable.

The information contained herein is to the best of our knowledge true and correct and any suggestions are made without guarantee, express or implied, since the conditions of use are beyond our control. *Craig Adhesives & Coatings* disclaims any liability incurred in connection with the use of these data or suggestions. Nothing contained herein shall be construed as a recommendation to infringe on any existing patents covering any material or its use.